

Tuscany Collection

Specifications



Tuscany Collection Specifications

 Construction: Engineered High Density Ply Core Hardwood with Tongue and Groove	 Edge Profile: 1-2mm Micro Beveled Edges and Ends
 Species: French Oak	 Installation: Nail, Staple, Glue, Float; Above Grade, At Grade, Below Grade
 Dimensions: 1/2" (Nominal overall thickness) X 7-1/2" (width) X 75" (70% long boards)	 Surface Treatment: Wire Brushed
 Thickness of Surface Layer: 2mm	 Gloss: <10 degree
 Cutting Method: Sliced Face	 Fire Testing ASTM E648 and ASTM E662 Results: Class I ASTM E84 Result: Class B
 Grade: ABCDEF	 Color Variation: Moderate Color Variation, Water Based Color

Finish:

8 coats of Enhanced Ultra Low Gloss Urethane finish with advanced aluminum oxide technology. Color depth through smoking and aging multi-step treatment and hand stained for weathered patina. On-trend colors.

Assembling Gap: $\leq 0.20\text{mm}$

Length Deviation: $\pm 0.5\text{mm}$

Width Deviation: $\pm 0.15\text{mm}$

Thickness Deviation: $\pm 0.2\text{mm}$

Reactive Stain: Yes

Surface Abrasion Resistance: $\geq 300\text{r}$, S-42 Sand paper

Film Hardness: $\geq 2\text{H}$

Static Bending Strength: $\geq 30\text{MPa}$

Moisture Content: 6%-9%



Packaging

Area per carton: 23.44 Sqft. per Carton

Weight per carton: 37.48 Lbs

Warranties: 50 year residential finish warranty, 5 year commercial warranty. Please visit www.palmettoroadfloors.com for the most current warranty information.



Environmental

Certifications: Floor Score Certified

Carb II Compliant: Yes

Lacy Act Compliant: Yes